


Voltage rectifier (AUX), output voltage 24 or 12 VDC – 20 W

Type: PN 230AC – 24, PN 230AC – 12

Technical data

| Type | PN 230 - 24 | PN 230 - 15 | PN 230 - 12 |
|---------------------------|---|-------------|-------------|
| Input voltage: | 230 V, 50 Hz | | |
| Input voltage deviation | + 20 %, - 20 % | | |
| Output voltage: | 24 VDC | 15 VDC | 12 VDC |
| Output stability | 0,5 % | | |
| Valovitost: | 0,5% pp | | |
| Adjustment Uo: | ± 10 % | | |
| Output power: | 20 W | | |
| Current limit: | 0,8 A | 1,3 A | 1,6 A |
| Over current limit: | IU | | |
| Soft start: | Yes | | |
| Input protection: | Over voltage, under voltage, over current | | |
| Izlazne zaštite: | Over voltage, over current | | |
| Short current protection: | Yes | | |
| Work frequensy:: | 100 kHz | | |
| Efficiency: | > 0,9 | | |
| Galvanic separation: | input - output - case: 1,5 kV, 50 Hz, 1 min | | |
| Indication: | Input voltage – LED, Output voltage – LED | | |
| Signalisation: | Eror – relay COM NO NC | | |
| Norms: | EN 60950 | | |
| Temperature ambient: | -15°C to +50°C | | |
| Cooling: | natural | | |
| Case: | DIN RAIL | | |
| IP protection: | IP 20 | | |
| Connections: | Row terminal | | |
| Dimensions (w x h x d): | 22 x 110 x 110 mm | | |



Created: K. Pavić, dipl.ing.el.

Reviewed: V. Hlušićka, ing.el.

Approved: M. Štević, ing.el.

| | | | | | |
|--|---|---------------|---|--------|-------------|
| MARETON POWER ELECTRONIC ZAGREB - CROATIA | Voltage rectifier – AUX 24 or 12 VDC – 20 W Type: PN 230AC – 24 / 12 | Rev.: | 2 | Dat | 28.05.2012. |
| | | 01-470-90-051 | | Page: | 1 |
| | | | | Pagec: | - |
| | | File: | | | |